



NOTES:

1. INCOMER TERMINATION DISTANCE: 370mm
FITTED WITH BARE CABLE CONNECTORS FOR 2x35-240mm PER PHASE.
2. DISTRIBUTION TERMINATION DISTANCE: 550mm
FITTED WITH 40x6mm BARS WITH M10x50mm BOLTS.
3. FITTED WITH ALUMINIUM GLAND PLATES SUITABLE FOR SINGLE CABLES.
4. ENCLOSURE FINISH: DARK ADMIRALTY GREY BS4800 18B25.
5. INGRESS PROTECTION: IP55.

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT, WITHOUT THEIR WRITTEN CONSENT, BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.

REV: -	EDR: -	MATERIAL: MILD STEEL	BASED ON: A7293056
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. EWM REFERS TO ENGINEERING & WORKSHOP MANUAL TOLERANCES TO EWM SECTION 3.1.3 FIXING STD TO EWM APPENDIX D. WIRING STD EWM SECTION 4. WELDING STANDARD TO QAI 061.		REF: S141468/9	COPY ISSUED
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK		ORIGINAL SCALE: 1:4	DATE: 13/03/23
TITLE: GENERAL ASSEMBLY MCO/1400-4P/IP55 & MCO/1630-4P/IP55		DRN. P.R.	DRAWING No. A37616
		CHKD.	REVISION
		APPD:	