



- NOTES:**
1. MILD STEEL ENCLOSURE FITTED WITH RAIN CANOPY & REMOVABLE ALUMINIUM GLAND PLATES.
 2. ENCLOSURE FINISH: DARK ADMIRALTY GREY (BS4800 18B25).
 3. TERMINATION DISTANCE: 422mm (RECOMMENDED DISTANCE FOR 300mm CABLE).
 4. CONNECTIONS: M10 LUG, MAX PALM WIDTH: 25mm EARTH CONNECTION: M16 LUG.
 5. INGRESS PROTECTION: IP55.
 6. INSET PLATES PROVIDE IP2X PROTECTION WHEN DOORS ARE OPEN.
 7. WEIGHT: 120KG APPROX.

CUSTOMER INFORMATION COPY



REV: -	EDR: -	MATERIAL: MILD STEEL	BASED ON: S010098
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. EWM REFERS TO ENGINEERING & WORKSHOP MANUAL TOLERANCES TO EWM SECTION 3.1.3 FIXING STD TO EWM APPENDIX D. WIRING STD EWM SECTION 4. WELDING STANDARD TO QAI 061.		REF: S010113	COPY ISSUED
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK		ORIGINAL SCALE: 1:4	
TITLE: GENERAL ASSEMBLY AMF500/DSC		DATE: 17/10/23	
DRN. P.R.	CHKD. [Signature]	DRAWING No. A38203	
APPD. [Signature]			REVISION