



NOTES:

1. MILD STEEL ENCLOSURE FITTED WITH RAIN CANOPY & REMOVABLE ALUMINIUM GLAND PLATES.
2. ENCLOSURE FINISH: DARK ADMIRALTY GREY (BS4800 18B25).
3. TERMINATION DISTANCE: 388mm (RECOMMENDED DISTANCE FOR 300mm CABLE).
4. CONNECTIONS: M12 LUG, MAX PALM WIDTH: 38mm INCOMER, 50mm DISTRIBUTION. EARTH CONNECTIONS: M10 & M16 LUG.
5. INGRESS PROTECTION: IP55.
6. INSET PLATES PROVIDE IP2X PROTECTION WHEN DOORS ARE OPEN.
7. WEIGHT: 145KG APPROX.

CUSTOMER INFORMATION COPY



THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT, WITHOUT THEIR WRITTEN CONSENT, BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.

REV: -	EDR: -	UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. EWM REFERS TO ENGINEERING & WORKSHOP MANUAL TOLERANCES TO EWM SECTION 3.1.3 FIXING STD TO EWM APPENDIX D. WIRING STD. EWM SECTION 4. WELDING STANDARD TO QM 061.	MATERIAL MILD STEEL	BASED ON A7194410
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK			REF. S010115	COPY ISSUED
TITLE GENERAL ASSEMBLY AMF800/DSC			ORIGINAL SCALE 1:5	DATE 06/11/23
DRN. CHKD. APPD.	P.R.		BLAKLEY ELECTRICS	REVISION
			A38217	