



CUSTOMER INFORMATION COPY

NOTES:

1. WIRING CABLE, END TERMINALS, SLEEVES AND OTHER CONSUMABLES ALL AS REQUIRED.
2. USE PIN CONNECTOR TERMINALS FOR TRANSFORMER PRIMARY FLYING LEADS.
3. F4* HANDLE FIXINGS WITHOUT SHAKEPROOF/SPRING WASHER AND TIGHTEN TO 30Nm OF TORQUE.
4. F1* WASHER ON THIS FIXING TO BE 1/4" TABLE 3 LIGHT CODE S260066 & USE SPRING WASHERS.
5. NYLON RIVET (Ø3.5) USED ON DOLLY FRAME Ø3.5 OPTIONAL BLANKING PLATE FIXING HOLES.

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT, WITHOUT THEIR WRITTEN CONSENT, BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.

REV:	A	B	C							
EDR:	6793	7619	7798							
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. TOLERANCES TO H30052 FIXING STANDARD TO H30051 WIRING STANDARD TO H20051 WELDING STANDARD TO QAI 61.							MATERIAL		SIZE	
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK							REF. S210340	COPY ISSUED		07 Nov 2019
TITLE							ORIGINAL SCALE	DATE		BLAKLEY ELECTRICS LIMITED DRAWING No. B28147 REVISION C
GENERAL ASSY. FOR TA/AI-S1/P/3/10/S6							1:5	07/11/19		
							DRN. B.W.			
							CHKD.			
							APPD.			SHEET 1 OF 1