



NOTES:
 INCOMER TERMINATION DISTANCE – 415mm
 INCOMER MAX CABLE ACCEPTANCE – M8 LUG CONNECTION MAX PALM WIDTH 25mm
 IP RATING – IP54

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT, WITHOUT THEIR WRITTEN CONSENT, BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.

CUSTOMER INFORMATION COPY

REV: -																			
EDR: -																			
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. TOLERANCES TO H30052 FIXING STANDARD TO H30051 WIRING STANDARD TO H20051 WELDING STANDARD TO QAI 061.													MATERIAL		SIZE				
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK													REF. S201151/2R		COPY ISSUED 18 Mar 2020				
TITLE GENERAL ASSEMBLY SRC 160-200A kWhr													ORIGINAL SCALE 1:5		BLAKLEY ELECTRICS LIMITED DRAWING No. B32395 REVISION				
													DATE. 20/02/20						
													DRN. P.R.						
													CHKD.						
													APPD. [Signature]						