



NOTES:

- DRAWING SHOWS B3 MDA TYPICAL ENCLOSURE WITH DOLLY COVER DESIGNED TO IP55.
- FITTED WITH REMOVABLE GLAND PLATES AND SOCKET PLATES.
- FIT LABELS IN POSITIONS AS DETAILED
- THE USE OF SWITCHED AND INTERLOCKED SOCKETS AT 63A IS TO COMPLY WITH THE REQUIREMENTS OF BS7375: DISTRIBUTION OF ELECTRICITY ON CONSTRUCTION AND DEMOLITION SITES.
- MAXIMUM RECOMMENDED CABLE SIZE: 150mm 4C SWA USING NARROW PALM CABLE LUGS.

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT WITHOUT THEIR WRITTEN CONSENT BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.

REV:	-																						
EDR:	-																						
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. TOLERANCES TO H30052 FIXING STANDARD TO H30051 WIRING STANDARD TO H20051 WELDING STANDARD TO QAI 061.												MATERIAL		MILD STEEL		SIZE							
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK												REF.		S140526		COPY ISSUED		19 Nov 2019					
TITLE												ORIGINAL SCALE		1:10		DATE		07/11/19		BLAKLEY ELECTRICS LIMITED			
GENERAL ASSEMBLY B3/1250-4P/C8-RCD S12-63/S6-32/IP55												DRN.		P.R		DRAWING No.		C27998		REVISION			
												CHKD.											
												APPD.		PWA									