



**GENERAL**

- FRONT COVER FIXED WITH M5 'ALLEN' SCREWS
- SOCKET FIXED WITH M4 'ALLEN' SCREWS
- METAL CLAD 32A 230V 2P+E IP44 BSEN60309-2 SOCKET OUTLET
- ALL GASKETS - TR5 FLAME RETARDANT
- ALL WIRING - BS7211 OHLS CABLE
- DOLLY COVER FIXED TO FRONT PLATE WITH 4No. M3. FIXINGS
- FIX 3 LABELS IN POSITIONS SHOWN
- SECTION 12 COMPLIANT ENCLOSURE

**FINISH**

- BACK BOX - WHITE - LUL APPROVED PAINT SYSTEM
- DOLLY COVER - WHITE
- FRONT PLATE: -
- ALT 1 VITREOUS ENAMEL COLOUR TO MATCH EXISTING TILES
- ALT 2 WHITE - LUL APPROVED PAINT SYSTEM
- ALT 3 BRUSHED STAINLESS STEEL

**CUSTOMER INFORMATION COPY**

REV: A	EDR: 8023	MATERIAL	SIZE
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. TOLERANCES TO H30052 FIXING STANDARD TO H30051 WIRING STANDARD TO H20051 WELDING STANDARD TO QAI 61.		REF. S120315	COPY ISSUED 01 Mar 2021
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK		ORIGINAL SCALE 1:3	<b>BLAKLEY ELECTRICS LIMITED</b>
TITLE GENERAL ASSY LV9*/230V/S/I/LUL 32A SOCKET		DATE 25/02/21	
DRN. A.H	CHKD.	DRAWING No. C28140	REVISION A
APPD.	SHEET 2 OF 3		

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT WITHOUT THEIR WRITTEN CONSENT BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.