



- NOTES:**
- OVERALL IP: IP55.
  - FINISH: HOT DIP GALVANISED
  - MAXIMUM INPUT CABLE SIZE – 4mm<sup>2</sup>.
  - OUTPUT WIRING TERMINATES DIRECTLY ON THE FUSEHOLDER (10mm<sup>2</sup> MAX)

**CUSTOMER INFORMATION COPY**

REV:	A	B								
EDR:	7944	7992								
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. TOLERANCES TO H30052 FIXING STANDARD TO H30051 WIRING STANDARD TO H20051 WELDING STANDARD TO QAI 061.						MATERIAL		SIZE		
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK						REF. S210379		COPY ISSUED		10 Dec 2020
TITLE						ORIGINAL SCALE		DATE		<b>BLAKLEY ELECTRICS LIMITED</b> DRAWING No. C34212 REVISION B
GENERAL ASSY STH/I/1/0.5/F6/GALV/ BST						1:4		10/12/20		
						DRN. A.H				
						CHKD.				
						APPD. RWA				

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT WITHOUT THEIR WRITTEN CONSENT BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.