



6A 110V IP67 FLORI-67 PLUG OPTION
REFER TO WD1745 FOR FURTHER INFORMATION
SEE TABLE BELOW FOR ADAPTER LEAD OPTIONS

T-BOX OPTION
SEE TABLE BELOW FOR ADAPTER LEAD OPTIONS

NOMINAL 2M LEAD
1.5mm² LSOH -25°C COLD WEATHER FLEXIBLE CABLE

NOMINAL 1M LEAD
1.5mm² LSOH -25°C COLD WEATHER FLEXIBLE CABLE

**CUSTOMER
INFORMATION
COPY**

NOTE: EMERGENCY FITTINGS ARE SUPPLIED WITH RED CABLE GLANDS
NON EMERGENCY FITTINGS ARE SUPPLIED WITH BLACK CABLE GLANDS

ITEM No	DESCRIPTION
S060916H	FLORI-67/3P/LP/27W/LED 27W LED ACF
S060917H	FLORI-67/3P/LP/27W/LED/EMER 27W EMERGENCY LED ACF
S060920H	FLORI-67/4P/LP/27W/LED 27W LED ACF
S060921H	FLORI-67/4P/LP/27W/LED/EMER/3C 27W LED ACF (RED, UNSWITCHED)
S060922H	FLORI-67/4P/LP/27W/LED/EMER/4C 27W LED ACF (GREEN, SWITCHED)
S060926H	ACL/LP/110/27W/LED/T-BOX 27W LED ACF
S060928H	ACL/LP/110/27W/LED/EMER/T-BOX/4C 27W EMERGENCY LED ACF

REV: -																	
EDR: -																	
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. EWM REFERS TO ENGINEERING & WORKSHOP MANUAL TOLERANCES TO EWM SECTION 3.1.3 FIXING STD TO EWM APPENDIX D. WIRING STD EWM SECTION 4. WELDING STANDARD TO QAI 061.						MATERIAL						BASED ON					
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK						REF.						COPY ISSUED 23 Jun 2022					
TITLE						ORIGINAL SCALE 1:6											
110V LED ACF FITTINGS 2ft TWIN						DATE. 22/06/22											
						DRN. PR						DRAWING No. C37007					
						CHKD.						REVISION					
						APPD. BWA						SHEET 1 OF 1					

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT WITHOUT THEIR WRITTEN CONSENT BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.