



- NOTES:**
- ENCLOSURE MATERIAL = 1.5mm MILD STEEL, WITH ZINC PHOSPHATE PRE-TREATMENT FOLLOWED BY WHITE POLYESTER POWDER COATING.
  - ASSEMBLY INGRESS PROTECTION MEETS IP44.
  - MAXIMUM INCOMING/OUTGOING CABLE SIZE = 16mm<sup>2</sup> VIA M25 KNOCK-OUTS.

**CUSTOMER INFORMATION COPY**

REV: -																													
EDR: -																													
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. EWM REFERS TO ENGINEERING & WORKSHOP MANUAL TOLERANCES TO EWM SECTION 3.1.3 FIXING STD TO EWM APPENDIX D. WIRING STD EWM SECTION 4. WELDING STANDARD TO QAI 061.										MATERIAL										BASED ON									
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK										REF. S050236A/255A/369A/483A										COPY ISSUED <b>18 Jan 2023</b>									
TITLE GENERAL ASSEMBLY FOR ELE/1/C*/30/A (UP TO 63A)										ORIGINAL SCALE 1:3																			
										DATE 18.01.23																			
										DRN. B.W.										REVISION									
										CHKD.																			
										APPD. <i>BWA</i>																			

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT WITHOUT THEIR WRITTEN CONSENT BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.