



- NOTES:**
- ENCLOSURE MATERIAL = 1.5mm MILD STEEL, WITH ZINC PHOSPHATE PRE-TREATMENT FOLLOWED BY WHITE POLYESTER POWDER COATING.
 - ASSEMBLY INGRESS PROTECTION MEETS IP44.
 - MAXIMUM INCOMING/OUTGOING CABLE SIZE = 35mm² VIA 2x M32 PUNCHED HOLES.

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT WITHOUT THEIR WRITTEN CONSENT BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.

REV: -												
EDR: -												
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. EWM REFERS TO ENGINEERING & WORKSHOP MANUAL TOLERANCES TO EWM SECTION 3.1.3 FIXING STD TO EWM APPENDIX D. WIRING STD EWM SECTION 4. WELDING STANDARD TO QAI 061.						MATERIAL MILD STEEL		BASED ON				
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK						REF. S050261	COPY ISSUED 14 Jul 2023					
TITLE GENERAL ASSEMBLY ELE/4P/C100/30/A TYPE A RCD						ORIGINAL SCALE 1:4						
						DATE 06/07/23				DRAWING No. C37926		
						DRN. P.R.				REVISION		
						CHKD.						
						APPD. <i>sh</i>						