



CUSTOMER INFORMATION COPY

- NOTES:**
- INGRESS PROTECTION: IP66.
 - PAINT FINISH: DARK ADMIRALTY GREY BS4800 18B25.
 - CABLE ENTRY: TOP & BOTTOM REMOVABLE GLAND PLATES.
 - MAXIMUM CABLE ACCEPTANCE: 50mm RIGID, 35mm FLEXIBLE.
 - INSET PLATE PROVIDES IP2X PROTECTION WHEN DOOR OPEN.

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT WITHOUT THEIR WRITTEN CONSENT BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.

REV:	-								
EDR:	-								
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. EWM REFERS TO ENGINEERING & WORKSHOP MANUAL TOLERANCES TO EWM SECTION 3.1.3 FIXING STD TO EWM APPENDIX D. WIRING STD EWM SECTION 4. WELDING STANDARD TO QAI 061.						MATERIAL MILD STEEL		BASED ON C31345	
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK						REF. S040394A	COPY ISSUED 27 Nov 2023		
TITLE GENERAL ASSEMBLY DB366/1100-2P/11W/ C10-16/110V						ORIGINAL SCALE 1:6			
						DATE. 22/11/23			
						CHKD.			
						APPD.			