



- NOTES:**
1. FITTED WITH 2kVA 110/230v TRANSFORMER.
 2. THE ENCLOSURE IS PHOSPHATE PRE-TREATED PRIOR TO POWDER COATING.
 3. ENCLOSURE FINISH: BS4800 18B25 DARK ADMIRALTY GREY.
 4. FITTED WITH 2M 1.5mm² 3C YELLOW PVC ARCTIC GRADE CABLE COMPLETE WITH A 16A 2P+E 110v PLUG.
 5. IP RATING: IP21
 6. WEIGHT: 26KG

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT WITHOUT THEIR WRITTEN CONSENT BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.

REV:	-																			
EDR:	-																			
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. EWM REFERS TO ENGINEERING & WORKSHOP MANUAL TOLERANCES TO EWM SECTION 3.1.3 FIXING STD TO EWM APPENDIX D. WIRING STD EWM SECTION 4. WELDING STANDARD TO QAI 061.												MATERIAL MILD STEEL		BASED ON C14532						
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK												REF. S210254		COPY ISSUED						
TITLE GENERAL ASSEMBLY STLPC/2/RCD/S2												ORIGINAL SCALE 1:4								
												DATE. 08/02/24								
												DRN. P.R.		DRAWING No. C38406		REVISION				
												CHKD.								
												APPD.								