



VERSION '1' – SURFACE MOUNTING

GENERAL

- FRONT COVER FIXED WITH M5 'ALLEN' SCREWS
- SOCKET FIXED WITH M4 'ALLEN' SCREWS
- METAL CLAD 16A 110V 2P+E BSEN60309-2 SOCKET OUTLET
- ALL GASKETS – TR5 FLAME RETARDANT
- ALL WIRING – BS7211 OHLS CABLE
- MCB COVER FIXED TO FRONT PLATE WITH 4No. M3. FIXINGS
- FIX 3 LABELS IN POSITIONS SHOWN
- INGRESS PROTECTION: ENCLOSURE IP55/OVERALL ASSEMBLY REDUCED TO IP44 (DUE TO USE OF IP44 METAL CLAD SOCKET)
- SECTION 12 COMPLIANT ENCLOSURE
- RCBO AND RCD OPTIONS ARE SUITABLE FOR USE ON 110V (RLV) SYSTEMS WITH 55V TO EARTH
- RCBOs INCLUDE SHORT-CIRCUIT AND OVERLOAD PROTECTION IN BOTH POLES

FINISH

- BACK BOX – WHITE – LUL APPROVED PAINT SYSTEM
- MCB COVER – GOLDEN YELLOW TO MATCH SOCKET
- FRONT PLATE :-
- ALT 1 VITREOUS ENAMEL COLOUR TO MATCH EXISTING TILES
- ALT 2 WHITE – LUL APPROVED PAINT SYSTEM
- ALT 3 BRUSHED STAINLESS STEEL

CUSTOMER INFORMATION COPY

REV:	A	B	C	D	E	F	G	H	J	K	L	M
EDR:	2171	2210	2211	2220	2452	3926	4159	5469	5845	6557	6772	8023
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. TOLERANCES TO H30052 FIXING STANDARD TO H30051 WIRING STANDARD TO H20051 WELDING STANDARD TO QAI 61.						MATERIAL		-		SIZE		
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK						REF. STD		COPY ISSUED		01 Mar 2021		
TITLE						ORIGINAL SCALE 1:3		BLAKLEY ELECTRICS LIMITED				
GENERAL ASSY 'LV9'SKT VERSION 1 L.U.L.						DATE 25/02/21						
						DRN. B.JONES		SHEET 1 OF 4				
						CHKD.						
						APPD.						

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT, WITHOUT THEIR WRITTEN CONSENT, BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE.