



VERSION '2' - FLUSH MOUNTING (HORIZONTAL)

GENERAL

- FRONT COVER FIXED WITH M5 'ALLEN' SCREWS
- SOCKET FIXED WITH M4 'ALLEN' SCREWS
- METAL CLAD 16A 110V 2P+E BSEN60309-2 SOCKET OUTLET
- ALL GASKETS - TR5 FLAME RETARDANT
- ALL WIRING - BS7211 OHLS CABLE
- MCB COVER FIXED TO FRONT PLATE WITH 4No. M3. FIXINGS
- FIX 3 LABELS IN POSITIONS SHOWN
- INGRESS PROTECTION: ENCLOSURE IP55/OVERALL ASSEMBLY REDUCED TO IP44 (DUE TO USE OF IP44 METAL CLAD SOCKET)
- SECTION 12 COMPLIANT ENCLOSURE
- RCBO AND RCD OPTIONS ARE SUITABLE FOR USE ON 110V (RLV) SYSTEMS WITH 55V TO EARTH
- RCBOs INCLUDE SHORT-CIRCUIT AND OVERLOAD PROTECTION IN BOTH POLES

FINISH

- BACK BOX - WHITE - LUL APPROVED PAINT SYSTEM
- MCB COVER - GOLDEN YELLOW TO MATCH SOCKET
- FRONT PLATE :-
- ALT 1 VITREOUS ENAMEL COLOUR TO MATCH EXISTING TILES
- ALT 2 WHITE - LUL APPROVED PAINT SYSTEM
- ALT 3 BRUSHED STAINLESS STEEL

CUSTOMER INFORMATION COPY

REV:	A	B	C	D	E	F	G	H	J	K	L	M
EDR:	2171	2210	2211	2220	2452	3926	4159	5469	5845	6557	6772	8023
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. TOLERANCES TO H30052 FIXING STANDARD TO H30051 WIRING STANDARD TO H20051 WELDING STANDARD TO QAI 61.						MATERIAL			SIZE			
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK						REF. STD			COPY ISSUED 01 Mar 2021			
TITLE						ORIGINAL SCALE 1:3			BLAKLEY ELECTRICS LIMITED			
GENERAL ASSY 'LV9'SKT VERSION 2 L.U.L.						DATE 25/02/21			DRAWING No. C6210S2			
						DRN. B.JONES			REVISION M			
						CHKD.						
						APPD.			SHEET 2 OF 4			

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT, WITHOUT THEIR WRITTEN CONSENT, BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE.